



07 P


with tube



Loose / Box [-50]



Taped / Reel [-51]



Part No	Inductance	f _L	Tol	Q	f _a	SRF	DCR	Rated DC Current
	L (µH)	(MHz)	± (%)	min	(MHz)	min (MHz)	max (Ω)	
07P-101X-YY	100	0.02	5,10	60	0.796	5.0	0.50	460
07P-151X-YY	150	0.02	5,10	70	0.796	4.0	0.85	350
07P-201X-YY	200	0.02	5,10	80	0.796	3.2	1.00	320
07P-221X-YY	220	0.02	5,10	80	0.796	3.0	1.00	320
07P-251X-YY	250	0.02	5,10	75	0.796	2.8	1.20	300
07P-681X-YY	680	0.02	5,10	80	0.796	2.3	3.70	170
07P-821X-YY	820	0.02	5,10	80	0.796	2.1	4.10	160
07P-102X-YY	1000	0.02	5,10	100	0.252	1.8	5.40	150
07P-122X-YY	1200	0.02	5,10	100	0.252	1.6	5.80	140
07P-152X-YY	1500	0.02	5,10	100	0.252	1.5	6.50	130
07P-182X-YY	1800	0.02	5,10	100	0.252	1.4	7.50	120
07P-222X-YY	2200	0.02	5,10	100	0.252	1.3	8.80	110
07P-272X-YY	2700	0.02	5,10	100	0.252	1.2	9.80	100
07P-332X-YY	3300	0.02	5,10	100	0.252	1.1	13.0	80
07P-392X-YY	3900	0.02	5,10	100	0.252	1.0	16.5	75
07P-472X-YY	4700	0.02	5,10	100	0.252	0.9	18.5	70
07P-562X-YY	5600	0.02	5,10	100	0.252	0.8	21.0	60
07P-682X-YY	6800	0.02	5,10	100	0.252	0.7	29.0	55
07P-822X-YY	8200	0.02	5,10	100	0.252	0.65	33.0	50

Core Material : Ferrite

Revision date : 11 Mar 2020

SPQ :

Packing Form	Loose / Box	Taped / Reel
Radial	500 [-50]	700 [-51]

Remarks: - Also available without tube.
- Also available with shorter leads.